



Coelho da Silva

Plasma⁽⁻⁾

| DATASHEET

TECHNICAL CHARACTERISTICS

APPLICABLE NORM: EN 1304

Clay roofing tiles for discontinuous laying. Product definitions and specifications.

	TEST	APPLICABLE STANDARD	STANDARD REQUIREMENTS	ACCOMPLISH
	EN 538	Flexural strenght	Resistance $\geq 1000N$	✓
	EN 539-1	Impermeability	(Method 2) Category 1	✓
	EN 539-2	Frost resistance	European single test method Resistant - Level 1 (≥ 150 cycles)	✓
	EN 1024	Geometric characteristics	Planarity $\leq 1,5\%$ Rectilinearity $\leq 1,5\%$	✓ ✓

DIMENSIONAL CHARACTERISTICS

ROOF TILE DIMENSIONS (approx.):

Anthracite, Slate, Steel Grey, Metallic Grey, Brown	Natural Red, Pearl White, Copper Green, Weathered, Natural Glazed
48,7 x 25,1 cm	49,1 x 25,3 cm

ROOF TILE WEIGHT (approx.):

4,000 kg

ROOF TILES PER m² (approx.):

12,5

GAUGE:

Recom.: 38,5 cm

Colours: Natural Red, Natural Glazed, Weathered, Brown,
Anthracite, Steel Grey, Copper Green, Pearl White,
Metallic Grey, Slate



CS Coelho da Silva, SA
Albergaria, 2480-071 Juncal, Portugal
tel. +351 244 479 200 | info@coelhodasilva.com

coelhodasilva.com

DESDE
SINCE 1927

17.06.2025
All rights reserved